



Increases labor savings and rooftop efficiencies when paired with the custom-fabricated Duro-Last Roofing System.



Compatible substrates include structural concrete, wood, polyisocyanurate rigid insulation board, and Duro-Guard® Cover Boards.



Full bond strength achieved within 24 hours of application.

DURO-LAST SOLVENT-GRIP SPRAY ADHESIVE PROPERTIES	
Consistency	Aerosol spray
Weight	40 lb. / cylinder
Spray Pattern	Variable web
Odor	Acetone smell
Base	Synthetic rubber and resin
Dry Time	3 – 5 minutes **
Service Temperature	-30° – 180° F
Flammability	Flammable when wet, non-flammable when dry
Shelf Life	12 months (unopened cylinder)
VOC Content	240.0 g / L (EPA method 24)
Prop 65	"WARNING! This product can expose you to chemicals which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov."

^{**} Depending upon climate conditions

For more information give us a call or visit our website today.

800-248-0280 duro-last.com

Duro-Last, Duro-Tuff, Duro-Guard, and the "World's Best Roof" are registered trademarks owned by Duro-Last, Inc. Solvent Grip Sell Sheet ORIG: 8.4.2020 - DL140053