



CADDY® PYRAMID
Rooftop Support System
for DURO-LAST®




 **DURO-LAST®**
THE WORLD'S BEST ROOF®

ERICO®

Hot-dip galvanized
for superior corrosion
protection

UV stabilized
for long lasting
performance



Foam bottom offers low
abrasion interface for better
roof membrane protection

Compatible with all
Duro-Last roofing
systems

CADDY® PYRAMID rooftop supports are a surface mounted solution for supporting electrical and mechanical applications.

They offer superior load capacity and dramatically reduce installation time by replacing slow, heavy and labor-intensive methods for support of pipe, conduit, duct, cable tray and equipment.

Unlike wood blocks, CADDY PYRAMID supports are specifically designed for rooftop applications, incorporating unique materials and finishes that protect the Duro-Last®, Duro-Fleece®, Duro-Last® EV, and Duro-Tuff® membranes while providing superior corrosion protection.

Applications

Plumbing & HVAC / Electrical /
Equipment Support


Challenges:

- Properly support heavy loads
- Minimize the chance of point loading or abrading the roof membrane
- Substandard materials and methods can increase the chance of roof damage
- Increasingly, roofs are seen as prime real estate and are being utilized for equipment placement, alternative energy systems, and as green space
- Meet the project scope and stay within budget
- Provide a high quality installation

CADDY PYRAMID Solutions:

- Offer a broad portfolio compatible with all Duro-Last roofing systems and standing seam metal.
- Provide excellent load distribution with some of the industry's best load ratings
- Minimize point loading and roof abrasion
- Are UV stable, corrosion resistant, and durable over an extensive temperature range
- Are fast and easy to install, minimizing costs
- Designed to get installers on and off the roof quickly
- Create an aesthetically pleasing, high quality solution

Rooftop Supports: Load Distribution



Product does not support load ratings at this level

CADDY® PYRAMID RL Roller-Based Supports

CADDY® PYRAMID RL Roller-Based Supports offer an ideal solution for mechanical piping systems. Long lasting performance is ensured by providing polymeric rollers for corrosion free rotation. CADDY PYRAMID RL Roller-Based Supports are specially designed to avoid formation of flat spots and seized rollers during expansion and contraction.

- Polymeric rollers ensure corrosion free rotation
- Foam bottom offers low abrasion interface for better roof membrane protection
- Compatible with all Duro-Last roofing systems and standing seam metal.
- Ready to use out of the box, saving installation time and labor
- Hot-dip galvanized and UV stabilized for long lasting performance
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credits



Provides a fixed height roller to support up to 6" schedule 40 nominal pipe.

- Roller-based support designed specifically for rooftop applications
- Roller capability allows longitudinal movement of pipe, resulting from thermal expansion or contraction

Material: Polyethylene, Polypropylene, Steel

Finish: Hot-dip galvanized

Temperature: -50 to 150 °F

Static Load Safety Factor: 3:1

Item Number	Pipe Size	Height	Static Load
21308	2" Max	5.80"	100 lb
21310	3" Max	6.25"	250 lb

CADDY® PYRAMID ST Strut-Based Supports



Provides a fixed-height mounting platform with multiple usable strut lengths.

- Provides superior support for pipe, conduit, duct, cable tray and equipment
- Multiple sizes and load ratings offer the ability to tailor the solution to the application
- Easy to transport to the roof
- Compatible with all Duro-Last roofing systems and standing seam metal.

Material: Polyethylene, Polypropylene, Steel


Finish: Hot-dip galvanized

Temperature: -50 to 150 °F

Static Load Safety Factor: 3:1

Item Number	Strut Length	Height	Static Load
21301	6"	4.8"	300 lb
21302	10"	4.8"	1,000 lb

CADDY® PYRAMID EZ Rubber-Based Supports



Feature a wide platform base design to provide reliable support and distribute load across roof surface. These versatile supports are fast and easy to install compared to wood blocks and metal straps.

- Quick height adjustment accommodates for uneven roofs or sloped condensate lines
- No tools or fasteners needed; fast snap-on installation
- Design sheds water and helps reduce pipe corrosion
- Roof-friendly; made of UV-stabilized material
- Compatible with all Duro-Last roofing systems and standing seam metal.

Item Number	Rigid Conduit/ Pipe Size	Height	Ultimate Static Load
21316	1"	1 3/4" – 4"	170 lb
21318	2"	4" – 6"	250 lb

Ultimate load at 1/4" (6.35 mm) deflection. Contact project or roofing engineer for maximum allowable load on individual project roof system.

Accessories



Single Piece Strut Clamp for Conduit

- One piece break apart strut for rigid conduit
- Includes thread impression and captured screw
- Multiple sizes available to accommodate 1/2" – 4" pipes



Rigid Strut Clamp for Pipe/Rigid Conduit

- One piece break apart strut clamp
- Includes thread impression and captured screw (1/2" thru 4" pipe size)
- Fits into open side of strut channel
- Conforms with Manufacturers Standardization Society (MMS) SP-58 (Type 59)
- Multiple sizes available to accommodate 1/2" – 8" pipes



800-248-0280 | www.duro-last.com

"Duro-Last", "Duro-Tuff", "Duro-Fleece", and the "World's Best Roof" are registered trademarks owned by Duro-Last, Inc.
Duro-Last Roofing Systems are proudly manufactured in the United States of America.
Pyramid Brochure 2.23.15_v1 / M#DL02-0018

DURO-LAST MAKES NO WARRANTIES WHATSOEVER FOR ANY ERICO PRODUCTS. THE ERICO WARRANTY IS OWNER'S SOLE REMEDY FOR ANY ALLEGED DEFECT OR FAILURE OF ANY ERICO PRODUCT. FURTHERMORE, DURO-LAST MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE (EITHER EXPRESS OR IMPLIED IN FACT, LAW, OR CUSTOM). FINALLY, DURO-LAST SHALL NOT BE RESPONSIBLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING BUT NOT LIMITED TO ANY LOSS OF PROFITS, LOSS OF USE OF THE BUILDING OR ANY DAMAGE TO THE BUILDING AND ITS CONTENTS AS A RESULT OF ANY ALLEGED DEFECT OR FAILURE OF AN ERICO PRODUCT OR CONTRACTOR'S WORKMANSHIP RELATED TO ANY ERICO PRODUCT.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.



WARRANTY

ERICO products are warranted to be free from defects in material and workmanship at the time of shipment. NO OTHER WARRANTY, WHETHER EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), SHALL EXIST IN CONNECTION WITH THE SALE OR USE OF ANY ERICO PRODUCTS. Claims for errors, shortages, defects or nonconformities ascertainable upon inspection must be made in writing within 5 days after Buyer's receipt of products. All other claims must be made in writing to ERICO within 6 months from the date of shipment or transport. Products claimed to be nonconforming or defective must, upon ERICO's prior written approval in accordance with its standard terms and procedures governing returns, promptly be returned to ERICO for inspection. Claims not made as provided above and within the applicable time period will be barred. ERICO shall in no event be responsible if the products have not been stored or used in accordance with its specifications and recommended procedures. ERICO will, at its option, either repair or replace nonconforming or defective products for which it is responsible or return the purchase price to the Buyer. THE FOREGOING STATES BUYER'S EXCLUSIVE REMEDY FOR ANY BREACH OF ERICO WARRANTY AND FOR ANY CLAIM, WHETHER SOUNDING IN CONTRACT, TORT OR NEGLIGENCE, FOR LOSS OR INJURY CAUSED BY THE SALE OR USE OF ANY PRODUCT.

LIMITATION OF LIABILITY

ERICO excludes all liability except such liability that is directly attributable to the willful or gross negligence of ERICO's employees. Should ERICO be held liable its liability shall in no event exceed the total purchase price under the contract. ERICO SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS OF BUSINESS OR PROFITS, DOWNTIME OR DELAY, LABOR, REPAIR OR MATERIAL COSTS OR ANY SIMILAR OR DISSIMILAR CONSEQUENTIAL LOSS OR DAMAGE INCURRED BY BUYER.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.